Panasonic

CV-CFW203L

Smart look Day/ Night Fixed Dome Camera with IR illuminator

Specifications



IR LED
day/night DIR removable
P66 standard

Key Features

- High-performance CMOS image sensor.
- Support 1080p@25fps (PAL)/ 30fps (NTSC)
- Support 75-3 coaxial cable (Belden 9259 or equivalent) transmission up to 500m.
- High speed & long distance real-time transmission.
- Support ICR for day time and night time operation.
- Support auto exposure, auto white balance, auto electronic shutter and auto gain function.
- Support DC12V power supply.
- IP66 compliance.


Standard Accessories


- Quick guide.....1 pc
- Important safety instruction.....1 pc

Parameter	CV-CFW203L		
Camera			
Image Sensor	1/2.9" 2.0 Mega Pixels CMOS		
Effective Pixels	1936 (H) x 1097 (V)		
Min Illumination	0.02Lux/ F2.0, 0Lux IR on		
Electronic Shutter	PAL : 1/25s~1/100,000s NTSC: 1/30s~1/100,000s		
Video Frame Rate	PAL : 25fps NTSC: 30fps		
Synchronization	Internal		
Day & Night	Auto (ICR)/ Color/ B/W		
Max IR Distance	30m		
Digital Noise Reduction	2D		
White Balance	Auto		
AGC	Auto		
BLC	Auto		
Lens			
Focal Length	3.6 mm		
Angular Field of View	H: 82.8° V: 44.2°		
Lens Type	M12		
Input / Output			
Video Output	1CH BNC HD-CVI video output		
General			
Power	DC 12V±25%		
Power Consumption	2.8W MAX		
Working Temperature	-30°C~+60°C. Less than 95% RH (no condensation)		
Dimensions	Φ93.4 mm × 79.7 mm		
Weight (approx.)	330g		
External Case	Metal		

*Refer to DVR spec sheet for recording frame rate limitation

Appearance





Important

- Safety Precaution: Carefully read the operating instruction manual before using this product.

- All pictures are simulated.
- Weights and dimensions are approximate.
- Specifications are subject to change without notice.
- These products may be subject to export control regulations.

DISTRIBUTED BY: