HD Analog Digital Video Recorder

Panasonic

CJ-HDR416

16 CH HDCVI 4 SATA HDD Analog Digital Video Recorder

Available Mar 2016




Key Features


- 16 CH with 1080p real time live view
- H.264 video encode
- 1/4/9/16 CH synchronous real time playback
- HDMI/ VGA/ TV simultaneous video output
- Support 4 SATA HDDs up to 24TB, 3 USB
- Digital Zoom in Live & Playback
- iPhone, iPad & Android

Standard Accessories

- Quick guide.....1pc
- Important safety instruction.....1 pc
- CD1pc

Appearance





Specifications		
Model		CJ-HDR416
Video/ Audio IF		
Video Input		16 CH, BNC
Туре	HDCVI	720p/ 1080p HDCVI
	Analog	NTSC/ PAL
Video Output		1 HDMI, 1 VGA, 1 TV
Audio Input		4 CH, BNC
Audio Output		1 CH, BNC
Two-way Talk		1 CH input, 1 CH output, BNC
Display		
Output Resolution		1920×1080, 1280×1024, 1280×720, 1024×768
Multiscreen Mode		1/4/8/9/16
Privacy Masking		4 rectangular zones (each camera)
OSD		Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Video/ Audio Format		
Video/Audio Compression		H.264/ G.711
Record Rate	Main Stream	1080P (1~12/15fps)/ 720P/ 960H/ D1/ HD1/ 2CIF/ CIF (1~25/30fps)
	Extra Stream	CIF/ QCIF (1~25/30fps), D1 (1~12/15fps)
Bit Rate		48~4096Kb/s
Record Mode		Manual, Schedule (Regular (Continuous), MD), Stop
Record Interval		1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Alarm/ Event		
Trigger Events		Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Spot, Snapshot, Buzzer & Screen tips
Video Detection		Motion Detection, MD Zones: 396 (22×18), Video Loss & Camera Blank
Playback & Backup		
Sync Playback		1/4/9/16
Search Mode		Time/Date, MD & Exact search (accurate to second)
Playback Functions		Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode		USB Device/ eSATA Device/ Network
Network		
Network Interface		RJ-45 port (10/100M/ 1000M)
Network Functions		HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P
Max. User Access		128 users
Mobile Device		iPhone, iPad, Android
HDD		
Туре		4 SATA ports, up to 24TB
External Interfac	e	
USB Interface		3 ports (2 Rear), USB2.0
RS485 Camera Interface		1 port RS485 for PTZ control,1 port RS422 for Keyboard
General Specifications		
Power Supply		AC 100~240 V, 50/60 Hz
Power Consumption		40W (without HDD)
Working Environment		-10°C~+55°C/ 10%~90%RH/ 86~106kpa
Dimension(W×D×H)		1.5U, 440mm×416mm×68mm
Weight		6KG (without HDD)

- All pictures are simulated.
- Weights and dimensions are approximate.
- Specifications are subject to change without notice.
- These products may be subject to export control regulations.

Important

- Safety Precaution: Carefully read the operating instruction manual before using this product.

DISTRIBUTED BY: