# **Panasonic**

# CV-CPW101AL

## Smart look Day/ Night Vari-Focal Box (Bullet) Camera with IR illuminator










### **Key Features**


- High-performance CMOS image sensor.
- Support 720p@25fps (PAL)/ 30fps (NTSC)
- Support 75-5 coaxial cable transmission up to 800m.
- High speed & long distance real-time transmission.
- Support ICR for day time and night time operation.
- Support auto exposure, auto white balance, auto electronic shutter and auto gain function.
- Support DC12V power supply.
- IP66 compliance.

#### **Standard Accessories**

•	Quick Guide1 pc
•	Important Safety Instruction1 pc
•	Hex Wrench 1 po

#### **Appearance**





## **Specifications**

Parameter	CV-CPW101AL		
Camera			
Image Sensor	1/3" 1.0 Mega Pixels CMOS		
Effective Pixels	1280 (H) x 720 (V)		
Min Illumination	0.05Lux/ F1.3, 0Lux IR on		
Electronic Shutter	PAL : 1/25s~1/100,000s NTSC: 1/30s~1/100,000s		
Video Frame Rate*	PAL : 25fps NTSC: 30fps		
Synchronization	Internal		
Day & Night	Auto (ICR)/ Color/ B/W		
Max IR Distance	30m		
Digital Noise Reduction	2D		
White Balance	Auto		
AGC	Auto		
BLC	Auto		
Lens			
Focal Length	2.7-13.5mm		
Angular Field of View	H: 27.6° (Tele) ~ 89° (Wide)		
Angulai i lelu di view	V: 16.2° (Tele) ~ 48° (Wide)		
Lens Type	M12		
Input / Output			
Video Output	1CH BNC HD-CVI video output		
General			
Power	DC 12V±25%		
Power Consumption	3W MAX		
Working Temperature	-40°C~+60°C. Less than 90% RH (no condensation)		
Dimensions	Φ 90.4 mm × 213.0 mm		
Weight (approx.)	550g		
External Case	Metal		

\*Refer to DVR spec sheet for recording frame rate limitation

#### Important

- Safety Precaution: Carefully read the operating instruction manual before using this product.
- All pictures are simulated.
- Weights and dimensions are approximate.
- Specifications are subject to change without notice.
- These products may be subject to export control regulations.

#### **DISTRIBUTED BY:**