

FaceStation2

Face recognition standalone controller



Key Features

- Ultra Performance
 - Matching speed - 1 : 3,000 match/sec
 - User capacity : Max. 30,000 users (1 : 1), 3,000 users (1 : N)
- Highest Operating Illuminance
 - Operating illuminance from 0Lux ~ 25,000Lux
- Enhanced Security
 - LFD (Live face detection) - IR-based image analysis to prevent spoofing by printed images and LCDs
 - Enhanced security by android 5.0 lollipop
 - High quality Image log
- Ergonomics & User Convenience
 - Extended height range - 145cm ~ 210cm
 - Improved face enrolment procedure

	FaceStation2
Biometric	Face
RFID Card	iCLASS SE / MIFARE CSN / DESFire EVI CSN
RF Read Range	50mm
CPU	1.4 GHz Quad Core
Memory	8GB Flash + 1GB RAM
LCD Type	4" color TFT LCD
LCD Resolution	800 x 480pixels
IR LED	140ea
Sound	24 bit Voice DSP (echo cancellation)
Operating Temperature	-20°C ~ +50°C (-4°F ~ +122°F)
Operating Humidity	0% ~ 80%, Non-condensing
Dimensions (WxHxD)	141 x 164 x 125mm (5.6" x 6.46" x 4.92")
Weight	Device : 548g (1.21 lb), Bracket : 74g (0.16 lb) (incl. washer and bolt)
Certicates	CE, FCC, KC, RoHS, REACH, WEEE, BT SIG
Power	24V DC / 2.5A
Image Dimension	720 x 480pixels
Live Face Detection	Supported
Max. User	30,000 (1 : 1), 3,000 (1 : N)
Max. Log	5,000,000 (text), 50,000 (image)
Wi-Fi	IEEE 802.11 b/g (FS2-AWB only)
Ethernet	10/100/1000Mbps
RS-485	1ea Host or slave (Selectable)
Wiegand	1ea input, 1ea output
TTL Input	1ea input
Relay	1ea
USB	USB 2.0 (Host)
Tamper	Available

* The latest product information / specification can be found at hanwha-security.com

* Design and specifications are subject to change without notice.

* Wisenet is the proprietary brand of Hanwha Techwin, formerly known as Samsung Techwin.